



NEWS 20/21



Lentejuelas / Lluentons / Sequins / Pailletten / Pailletes

EXPOSITOR · DISPLAY: nº 800
UNIDADES · UNITS: 18 pcs







Mullido /
Tou /
Fluffy /
Flauschig /
Duveteux



EXPOSITOR · DISPLAY: nº 801
UNIDADES · UNITS: 18 pcs



BORDADOS · EMBROIDERIES



EXPOSITOR · DISPLAY: nº 802
UNIDADES · UNITS: 12 pcs





EXPOSITOR · DISPLAY: nº 803
UNIDADES · UNITS: 12 pcs



Imitación piel / Imitació pell / Leather imitation / Lederimitation / Imitation cuir



BORDADOS • EMBROIDERIES

EXPOSITOR • DISPLAY: nº 804
UNIDADES • UNITS: 18 pcs



Imitación piel / Imitació pell / Leather imitation / Lederimitation / Imitation cuir

BORDADOS · EMBROIDERIES



EXPOSITOR · DISPLAY: n° 805
UNIDADES · UNITS: 18 pcs





EXPOSITOR · DISPLAY: nº 806
UNIDADES · UNITS: 12 pcs





EXPOSITOR · DISPLAY: nº 807
UNIDADES · UNITS: 12 pcs





COPYRIGHT

EXPOSITOR • DISPLAY: n° 808
UNIDADES • UNITS: 12 pcs





COPYRIGHT

EXPOSITOR • DISPLAY: n° 809
UNIDADES • UNITS: 12 pcs





ADORNOS TERMOADHESIVOS
y AUTOADHESIVOS
THERMOADHESIVE &
SELF-ADHESIVE ADORNMENTS
ORNEMENTS THERMO-ADHÉSIFS
ET AUTO-ADHÉSIFS



ref. 7141 (6 X 3 = 18 un)



ADORNOS TERMOADHESIVOS
y AUTOADHESIVOS
THERMOADHESIVE &
SELF-ADHESIVE ADORNMENTS
ORNEMENTS THERMO-ADHÉSIFS
ET AUTO-ADHÉSIFS



ref. 7142 (6 X 3 = 18 un)



CALIDAD ETIQUETA TEJIDA / QUALITY WOVEN LABEL / QUALITAT ETIQUETA TEIXIDA

ref. 7143 (6 X 3 = 18 un)



ref. 7144 (6 X 3 = 18 un)





ES. Colocar el parche en una superficie limpia. Aplicar calor con un secador de pelo o si la superficie lo permite, planchar durante 30 segundos para obtener resistencia al lavado.

GB. Stick on clean and untreated material. Heat up with hair dryer. For wash resistance iron for 30 seconds, if material is suitable for ironing.

FR. Coller sur une surface propre et non traitée. Chauffer la pièce avec un sèche cheveux. Repasser 30 sec a la pièce pour une meilleure adhérence si le support est adapté.

IT. Incollare su superficie pulita e non trattata, riscaldare con el phon. Per una maggiore tenuta nel lavaggio e se la superficie lo permette, stirare per 30 secondi.

DE. Auf unbehandelten, sauberen Untergrund kleben. Mit fön erwärmen. Für Waschfestigkeit 30 sek. aufbügeln, wenn Untergrund bügelbar.

PL. Przyklejać na czystej, suchej powierzchni. Rozgrzać suszarką. Dla utrzymania jakości podczas prania naprasowywać przez 30 sekund, jeśli warstwa spodnia nadaje się do prasowania.

Composición del tejido
Composition weave
100% PES



RIZAL, S.L.


C/ Sant Ferran, 237
08205 Sabadell · Barcelona · SPAIN
Telf. +34 93 725 18 88
info@rizaal.com
www.rizaal.com



CALIDAD ETIQUETA TEJIDA / QUALITY WOVEN LABEL / QUALITAT ETIQUETA TEIXID.



**ADORNOS TERMOADHESIVOS
y AUTOADHESIVOS
THERMOADHESIVE &
SELF-ADHESIVE ADORNMENTS
ORNEMENTS THERMO-ADHÉSIFS
ET AUTO-ADHÉSIFS**





RIZAAL S.L.

c/ Sant Ferran 237
08205-SABADELL
(Barcelona)



Tel. +34 937251888

Whatsapp: +34 625838000

info@rizaal.com

www.rizaal.com

